



www.detailedplaypro.com 877-548-3100

Playground Slides Specifications

PLASTICS (TUBES / SLIDES / HOODS)

- 1st quality linear low density Polyethylene (LDPE) – ExxonMobil LL8450
- Rotational molded
- 3/8" wall thickness
- 2,550 psi tensile strength (ASTM D638)
- Mold-in graphics
- UV stabilized
- UV 8 Rating (tested per ASTM G155 cycle 1 guidelines)
- Anti-static inhibitors
- 19 color options

SLIDE FOOT

- 3.5" O.D. support post
- Pre-treatment wash primer
- Powder coat finish

SLIDE SUPPORT

- 3.5" O.D. galvanized steel support post
- Post manufactured per ASTM 500
- Plate manufactured per ASTM A90, A568, A902, A924, D2092, E517, E646 and ISO3575
- Pre-treatment wash primer
- Powder coat finish

COATINGS

Powder Coating

- TGIC polyester
- Electrostatic application
- Baked-on @ 400 degrees
- 5-7 mills thick
- Lead free
- High gloss
- No peel / No flake finish
- Resistant to salt spray (ASTM B-117)
- Resistant to humidity (ASTM D-2247)
- Direct/Indirect impact 120 in. pounds (ASTM D-2794)
- Good to excellent resistance to most solvents, oils, acids and alkalis