



www.detailedplaypro.com 877-548-3100
Playground Swings Specifications

COMMERCIAL SWING SEATS

BELT SEAT

- 6" Wide
- Compression molded from EPDM co-polymer
- Steel inserts for strength and durability
- Galvanized hardware
- 5 color options

HALF BUCKET SEAT and FRONT SAFETY CHAIN

- Steel inserts for strength and durability
- Galvanized hardware
- 4 color options

FRONT SAFETY CHAIN

- Attaches to seat with S-hooks
- Closes with snap
- Protective plastic cover

FULL BUCKET SEAT

- One-piece co-polymer construction
- Steel inserts for strength and durability
- 5" wide band surrounds toddlers
- Galvanized hardware
- 5 color options

CHAIN (4/0)

- Hot dipped, galvanized for rust prevention (ASTM A-153)
- Zinc plated (ASTM B-633)
- Straight link coil
- Maximum working load limit 670 pounds (4/0 chain)
- Minimum ultimate break 2,680 pounds (4/0 chain)
- 0.85" OD – 0.414" ID (4/0 chain)
- 1.80" OAL (4/0 chain)

PLASTIC TIRE

- 1st quality linear low density Polyethylene (LDPE) – ExxonMobil LL8450
- Rotational molded
- 3/8" wall thickness
- 2,550 psi tensile strength (ASTM D638)
- Mold-in graphics
- UV stabilized
- UV 8 Rating (tested per ASTM G155 cycle 1 guidelines)
- Anti-static inhibitors