



www.detailedplaypro.com 877-548-3100
Swing Set Hardware Specifications

PIPE SWING HANGERS – DUCTILE IRON

- Grade 32510 hot-dipped, galvanized, malleable iron
- Manufactured per ASTM A339-55
- Rust proof
- Lubrication-free brass bearing
- Plated carriage bolts and machine bolts
- Will not twist on pipe
- 2-3/8" & 3-1/2" O.D. pipe
- Smooth, noiseless action

HEAVY DUTY TIRE SWIVEL

- Machined steel
- 90° universal cast steel joint covered by rubber boot
- Enamel coating
- Grease fittings for easy maintenance
- Secured with four plated machine bolts and nylon insert lock nut
- 3-point mounting system
- Sealed needle bearings

CHAIN (4/0)

- Hot dipped, galvanized for rust prevention (ASTM A-153)
- Zinc plated (ASTM B-633)
- Straight link coil
- Maximum working load limit 670 pounds (4/0 chain)
- Minimum ultimate break 2,680 pounds (4/0 chain)
- 0.85" OD – 0.414" ID (4/0 chain)
- 1.80" OAL (4/0 chain)

CLEVIS CONNECTOR

- Galvanized, forged steel
- Tamper resistant
- Galvanized hex pin shoulder bolt
- Special tool required for install